



Chemical Compatibility Chart

Build Your Own Berm™ and Drive Over Build Your Own Berm™

NOTICE:

This report is offered as a guide and was developed from information which, to the best of SpillTech's knowledge, was reliable and accurate. Due to variables and conditions of application beyond SpillTech's control, none of the data shown in this guide is to be construed as a guarantee, expressed, or implied. SpillTech assumes no responsibility, obligation, or liability in conjunction with the use or misuse of the information.

Ratings / Key or Ratings — Chemical Effect — Based on 7-day testing

A = Fluid has little or no effect

B = Fluid has minor to moderate effect

C = Fluid has severe effect

T = No data, likely to be acceptable

X = No data, not likely to be acceptable

Degradation may result from chemical incompatibilities. Discoloration or degradation may occur. Periodically inspect products when in use for proper seal. Due to variables and conditions beyond our control, SpillTech cannot guarantee that this product(s) will work to your satisfaction. To ensure effectiveness and your safety, we recommend that you conduct compatibility testing of your chemicals with this product prior to purchase. For additional questions or information, contact SpillTech.

Chemical Name	Rating
Acetone	B
Antifreeze (Ethylene Glycol)	A
Diesel Fuel	B
Ethyl Alcohol (Ethanol)	A
Gasoline	B
Hydraulic Oil	A
Hydrochloric Acid (20%)	B
Methyl Alcohol (Methanol)	A

Chemical Name	Rating
Methyl Ethyl Keytone (MEK)	C
Perchloroethylene	B
Salt Water (25%)	A
Sodium Hydroxide (60%)	A
Sodium Hypochlorite (Bleach)	A
Sulfuric Acid (96%)	C
Sulfuric Acid (36% - Battery Acid)	A
Toluene	C