

# Universal Launderable Sock #1010 - 3" x 48", 15 socks/package



Just wring out this economical Universal Sock and reuse it at least 40 times!

- Can be used over and over again, providing more than just great leak and spill containment — it's cost-effective as well
- Can do the work of up to 40 regular socks
- Durable, universal-application, polypropylene-filled socks absorb oils, coolants, solvents and water
- Good wherever you have a variety of spills and only want to stock one sock to cover everything
- Ideal for surrounding spilled fluids or wrapping around leaky machines
- Easy and convenient to put into place
- Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards
- Flexible to conform around machine bases and offer a snug fit with no seepage

## 1010 Specifications

 Dimensions:
 ext. dia. 3" x 48" L

 Shipping
 17" W x 24" L x 21" H

**Dimensions:** 

**Sold as:** 15 socks per package

Color: Blue

**Composition:** Polypropylene/KC Sontara **Absorbency:** Up to 9.8 gal. per package **Absorbency per:** Up to 41.8 oz. per sock

Weight: 45.94 lbs.

# per Pallet: 16
Incinerable: Yes
Ship Class: 175

## **Metric Equivalent Specifications**

**Dimensions:** ext. dia. 7.6cm x 122cm L **Shipping** 43cm W x 61cm L x 53cm H

**Dimensions:** 

Absorbency: Up to 37.1 L per package
Absorbency per: Up to 1.2 L per sock

Weight: 20.8 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

## 1010 Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

#### **Regulations and Compliance:**

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

### **Technical Documents:**

(Available at **spilltech.com**)
Product Data Sheet (PDS)

Safety Data Sheet (SDS)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com