

## 65-Gallon OverPack Salvage Drum #A65OVER - 28.25" dia x 37.5", 1 each/package



Stock a SpillTech® OverPack with sorbents for emergency spill response or use it as a salvage drum to ship damaged containers or hazardous waste.

- DOT-approved and X-rated for use as salvage drums
- Helps companies conform to federal regs when shipping damaged or leaking containers of hazardous materials or absorbents contaminated with hazardous substances
- Stores sorbent products (not included) for quick response and easy access as needed for spill control
- 100% polyethylene OverPack resists chemicals, rust and corrosion for years of use
- Integrated handles make them easy to lift, move or carry with standard material handling equipment
- Twist-on, double-wall lid with closed-cell gasket provides sealed, secure closure to prevent leaks and protect contents from moisture, dirt and damage
- Durable to withstand rough handling.
- We can customize a Spill Kit to your exact specifications, including the container, its contents and accessories, with no upcharge! Contact your local Distributor for details.

### A65OVER Specifications

<b>Dimensions:</b>	ext. dia. 28.25" x 37.5" H
<b>Shipping Dimensions:</b>	28.25" W x 37.37" L x 28.25" H
<b>Sold as:</b>	1 per package
<b>Color:</b>	Yellow
<b>Composition:</b>	Polyethylene
<b>Weight:</b>	45 lbs.
<b># per Pallet:</b>	8
<b>Incinerable:</b>	No
<b>UN RATING:</b>	1H2/X200/S
<b>Ship Class:</b>	250

### Metric Equivalent Specifications

<b>Dimensions:</b>	ext. dia. 71.8cm x 95.3cm H
<b>Shipping Dimensions:</b>	71.8cm W x 94.9cm L x 71.8cm H
<b>Weight:</b>	20.4 kg

## A65OVER Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

49 CFR 173.12(b)(2)(iv) - When labpacking, "Inner packagings...must be surrounded by a chemically compatible absorbent material in sufficient quantity to absorb the total liquid contents."

49 CFR 173.12(b) - A container used for labpacking must be "a UN 1A2 or UN 1B2 metal drum, a UN 1D plywood drum, a UN 1G fiber drum or a UN 1H2 plastic drum tested and marked at least for the Packing Group III performance level for liquids or solids."

### Technical Documents:

(Available at [spilltech.com](https://spilltech.com))

Product Data Sheet (PDS)

Chemical Compatibility (CCG)



Online:  
[spilltech.com](https://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)