

95-Gallon OverPack Salvage Drum #A95OVER - 32" dia x 41.5", 1 each/package



Stock a SpillTech® OverPack with sorbents for emergency spill response or use it as a salvage drum to ship damaged containers or hazardous waste.

- DOT-approved and X-rated for use as salvage drums
- Helps companies conform to federal regs when shipping damaged or leaking containers of hazardous materials or absorbents contaminated with hazardous substances
- Stores sorbent products (not included) for quick response and easy access as needed for spill control
- 100% polyethylene OverPack resists chemicals, rust and corrosion for years of use
- Integrated handles make them easy to lift, move or carry with standard material handling equipment
- Twist-on, double-wall lid with closed-cell gasket provides sealed, secure closure to prevent leaks and protect contents from moisture, dirt and damage
- Durable to withstand rough handling
- We can customize a Spill Kit to your exact specifications, including the container, its contents and accessories, with no upcharge! Contact your local Distributor for details

A95OVER Specifications

Dimensions:	ext. dia. 32" x 41.5" H
Shipping	31.75" W x 41.5" L x 31.75" H
Dimensions:	
Sold as:	1 per package
Color:	Yellow
Composition:	Polyethylene
Weight:	48 lbs.
# per Pallet:	8
Incinerable:	No
UN RATING:	1H2/X295/S
Ship Class:	250

Metric Equivalent Specifications

Dimensions:	ext. dia. 81.3cm x 105.4cm H
Shipping	80.6cm W x 105.4cm L x 80.6cm H
Dimensions:	
Weight:	21.8 kg

A95OVER Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

49 CFR 173.12(b)(2)(iv) - When labpacking, "Inner packagings...must be surrounded by a chemically compatible absorbent material in sufficient quantity to absorb the total liquid contents."

49 CFR 173.12(b) - A container used for labpacking must be "a UN 1A2 or UN 1B2 metal drum, a UN 1D plywood drum, a UN 1G fiber drum or a UN 1H2 plastic drum tested and marked at least for the Packing Group III performance level for liquids or solids."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Chemical Compatibility (CCG)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com