

Universal CornCob Sock #CCSO40 - 3" x 42", 40 socks/package



An affordable alternative to messy clay.

- Economical and highly efficient for even the toughest jobs
- Absorb 1/2 gallon of oil, coolants, solvents and water nearly twice as much as clay, but without the dust or the mess to clean up afterward-; incinerable
- Ideal for surrounding spilled fluids or wrapping around leaky machines
- USDA BioPreferred approved
- Product weight will vary, as socks are filled by volume

CCSO40 Specifications

Dimensions: ext. dia. 3" x 42" L **Shipping** 20" W x 25" L x 17" H

Dimensions:

Sold as: 40 socks per package

Color: Gray

Composition: Corn Cob Filler/Polypropylene Sleeve

Absorbency: Up to 20 gal. per package
Absorbency per: Up to .5 gal. per sock

Weight: 47 lbs.
per Pallet: 16
Incinerable: Yes
Ship Class: 100

Metric Equivalent Specifications

 Dimensions:
 ext. dia. 7.6cm x 106.7cm L

 Shipping
 50.8cm W x 63.5cm L x 43.2cm H

Dimensions:

Absorbency: Up to 75.7 L per package
Absorbency per: Up to 1.9 L per sock

Weight: 21.3 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

CCSO40 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at **spilltech.com**)
Product Data Sheet (PDS)
Safety Data Sheet (SDS)

