

Universal 50-Gallon Kit Refill #RSPKU-50 - Absorbs up to 45.7 Gallons



Refill your SpillTech® Universal 50-Gallon Spill Kit to ensure fast response.

RSPKU-50 Specifications

Dimensions:	20" W x 24" L x 20" H
Shipping	20" W x 24" L x 20" H
Dimensions:	
Sold as:	1 per package
Absorbency:	Up to 43.3 gal. per package
Weight:	30.45 lbs.
# per Pallet:	10
Incinerable:	Yes
Ship Class:	175
Includes:	100 - 15" x 19" Gray Universal HeavyWeight SonicBonded Pads (GPB100H) 6 - 3" x 4' Gray Universal Sorbent Socks (GSO430) 4 - 18" x 18" Gray Universal Sorbent Pillows (GPIL1818) 1 - 6" Glow Light Stick (A-LIGHTSTICKS) 1 - Emergency Response GuideBook (A-EGB) 5 - 18" X 30" Yellow Disposal Bags & Ties (A-DISPAG-SM) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A-KITLABEL) 6 - 6" X 2" TamperProof Seals (A-SEAL)

Metric Equivalent Specifications

Dimensions:	51cm W x 61cm L x 51cm H
Shipping	51cm W x 61cm L x 51cm H
Dimensions:	
Absorbency:	Up to 163.9 L per package
Weight:	13.8 kg



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

RSPKU-50 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com