

Universal Fleet Spill Kit #SPKU-FLEET - Absorbs up to 10.7 Gallons



Be prepared for fast response with a SpillTech® Universal Spill Kit!



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

SPKU-FLEET Specifications

Dimensions:	22" W x 20" L x 9" H
Shipping Dimensions:	20" W x 22" L x 9" H
Sold as:	1 per package
Absorbency:	Up to 10.7 gal. per package
Weight:	9.57 lbs.
# per Pallet:	32
Incinerable:	No
Ship Class:	92.5
Includes:	50 - 10" x 14" Gray Universal HeavyWeight FineFiber Pads (GPF1014H) 2 - 3" x 4' Gray Universal Sorbent Socks (GSO430) 1 - 1 lb. Plug & Dike Epoxy Putty (A-PND) 9 - Assorted Wooden Plugs (A-WOODPLUGS-LG) 2 - 18" X 30" Yellow Disposal Bags & Ties (A-DISP BAG-SM) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 8" x 17" x 20" Yellow Nylon "Spill Responder" Zippered Tote Bag (A-YTOTE)

Metric Equivalent Specifications

Dimensions:	56cm W x 51cm L x 23cm H
Shipping Dimensions:	51cm W x 56cm L x 23cm H
Absorbency:	Up to 40.5 L per package
Weight:	4.3 kg

SPKU-FLEET Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com