

Conical Drain Plug #DP3 - 3" dia. 1 each/package



Confidently block pollution without permanently sealing your drain. A reusable Conical DrainPlug fits conveniently under a drain's grate and pulls out easily to allow normal flow.

- Chemical-resistant polyurethane reliably seals drain to keep out unwanted liquids
- To install, just lift grate, press tapered conical Plug into drain and replace grate; to remove, pull up on metal ring using hand tools
- · Cleans easily with soap and water for reuse
- Non-permanent alternative to sealing drains with cement Note: Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Customer Service at 800.228.3877 or use our live chat feature. These products are for temporary use only. Pick up after each use, clean, then store properly. Do not leave down for extended periods of time or drive over with vehicles.

DP3 Specifications

 Dimensions:
 ext. dia. 3" x 5" H

 Shipping
 6" W x 6" L x 6" H

Dimensions:

Sold as: 1 per package

Color: Yellow

Composition: Polyurethane, Metal Eye Bolt

Weight: 1.5 lbs. # per Pallet: 500 Incinerable: No Ship Class: 70

Metric Equivalent Specifications

Dimensions: ext. dia. 7.6cm x 12.7cm H

Shipping 15.2cm W x 15.2cm L x 15.2cm H

Dimensions:

Weight: .7 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com

DP3 Technical Information

Warnings & Restrictions:

Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Customer Service at 800.228.3877 or use our live chat feature. These products are for temporary use only. Pick up after each use, clean, then store properly. Do not leave down for extended periods of time or drive over with vehicles.

Regulations and Compliance:

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com