



Provide large-scale containment that helps meet regulations with this durable, drive-in berm.

- Reinforced Coolguard® fabric resists rips, tears and punctures; highly durable for demanding applications
- Chemical-resistant berm is compatible with acids, water, oils and solvents
- Sidewalls are supported by wide-base hurdle brackets; larger support area offers maximum rigidity and stability
- Great for long-term containment of drums, totes, roll-offs, equipment and vehicles; also ideal for decon stations or response to tank leaks
- Reusable berm can be repaired if damaged; clean, fold and store for future deployment

BERM1250H Technical Information

Warnings & Restrictions:

Spill

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

Technical Documents:

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)



Online: spilltech.com

Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

6455 East Johns Crossing, Suite 375 • Johns Creek GA 30097 © 2024 SpillTech Environmental Corporation. All rights reserved.