

Containment Berm - L Bracket #BERM48L - 8' x 4' x 1', 1 each/package



Provide large-scale containment that helps meet regulations with this durable, drive-in berm.

- Reinforced Coolguard® fabric resists rips, tears and punctures; highly durable for demanding applications
- Chemical-resistant berm is compatible with acids, water, oils and solvents
- Sidewalls are supported by sturdy L-shaped composite brackets
- Great for long-term containment of drums, totes, roll-offs, equipment and vehicles; also ideal for decon stations or response to tank leaks
- Reusable berm can be repaired if damaged; clean, fold and store for future deployment

BERM48L Specifications

Dimensions: 4' W x 8' L x 1' H **Shipping** 21" W x 36" L x 13" H

Dimensions:

Sold as: 1 per package

Color: Black

Composition: Coolguard® Fabric 36 mil /

Composite Brackets

Sump Capacity: 239 gal. per package

Weight: 21 lbs. # per Pallet: 10 lncinerable: No Ship Class: 125

Metric Equivalent Specifications

Dimensions: 121.9cm W x 2.4m L x 30.5cm H **Shipping** 53.3cm W x 91.4cm L x 33cm H

Dimensions:

Sump Capacity: 904.6 L per package

Weight: 9.5 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

BERM48L Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

Technical Documents:

(Available at **spilltech.com**)
Product Data Sheet (PDS)
Safety Data Sheet (SDS)
Chemical Compatibility (CCG)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com