

Drive Over Build Your Own Berm® Wall Ends #DOBYOB-2WE - 3" x 5.5" x 2", 2/package



Contain and control liquid in high-traffic areas.

- Customizable containment barriers pop right back to form after vehicles, pallet jacks or dollies roll over them
- Berm compresses to approximately 1/4" when driven over; constructed of 40-ounce, vinyl-coated fabric with an open-cell foam core
- 2" height accommodates low-clearance traffic
- Durable enough to withstand indoor or outdoor traffic from trucks, loaded tow motors and other heavy vehicles

DOBYOB-2WE Specifications

Dimensions: 5.5" W x 3" L x 2" H

Shipping 9.25" W x 9.25" L x 6.5" H

Dimensions:

Sold as: 2 per package

Color: Orange

Composition: Cover - 40 oz. PVC

Core - Open-Cell Polyurethane Foam

Strips - Aluminum

Anchors - Galvanized Steel

Weight: 2 lbs.
per Pallet: 260
Incinerable: No
Ship Class: 125

Metric Equivalent Specifications

Dimensions: 14cm W x 7.6cm L x 5.1cm H

Shipping 23cm W x 23cm L x 17cm H

Dimensions:

Weight: .9 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

DOBYOB-2WE Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

Technical Documents:

(Available at **spilltech.com**)
Product Data Sheet (PDS)
Chemical Compatibility (CCG)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com