

## 1-Drum Spill Deck #DECK1 - 26" x 26" x 5.75" 1/package



Low-profile, modular Spill Decks let you design and create a containment system that meets your specific needs.

- NOTE: The Item number for this product has recently changed from ULT1321 to DECK1. Please make a note of it.
- 1-, 2- and 4-Drum Spill Decks can be used alone or are easily connected together with Bulkhead Fittings (BHFIT) and T-Strips (T-STRIP) to allow a virtually unlimited number of customized configurations
- Bulkhead fittings lock Spill Decks together while allowing spills to flow between Decks; can help you meet containment regulations depending on the size of container stored and the total sump capacity of the Deck system
- All-polyethylene construction meets a wide range of chemical compatibility needs
- Low height offers safe and convenient loading/unloading of drums
- Ideal for collecting hazardous waste, storing virgin chemicals or batteries, dispensing from drums and more
- Optional Loading Ramp (DECKRAMP) provides added drum handling safety and convenience

### DECK1 Specifications

<b>Dimensions:</b>	26" W x 26" L x 5.75" H
<b>Shipping</b>	27" W x 35" L x 7" H
<b>Dimensions:</b>	
<b>Sold as:</b>	1 per package
<b>Color:</b>	Yellow
<b>Composition:</b>	100% Polyethylene
<b>Load Capacity UDL:</b>	3000 lbs. per package
<b>Sump Capacity:</b>	11 gal. per package
<b>Weight:</b>	23 lbs.
<b># per Pallet:</b>	20
<b>Incinerable:</b>	No
<b>Ship Class:</b>	200

### Metric Equivalent Specifications

<b>Dimensions:</b>	66cm W x 66cm L x 14.6cm H
<b>Shipping</b>	68.6cm W x 88.9cm L x 17.8cm H
<b>Dimensions:</b>	
<b>Load Capacity UDL:</b>	1360.8 kg per package
<b>Sump Capacity:</b>	41.6 L per package
<b>Weight:</b>	10.4 kg

## DECK1 Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

### Technical Documents:

(Available at [spilltech.com](https://spilltech.com))

Product Data Sheet (PDS)



Online:  
[spilltech.com](https://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)