

SpillTech

5440 McGinnis Village Place Suite 102 Alpharetta, GA 30005 Phone: 1-800-228-3877

Fax: 1-800-872-3764 www.spilltech.com

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: 1010 and 1011

CHEMICAL FAMILY: Universal Reusable Socks

MANUFACTURER'S NAME: SpillTech

Company Profile:

SpillTech Brookley Industrial Complex 1627 O'Donoghue Street Mobile, AL 36615

Customer Service Telephone Number: 1-800-228-3877

Technical Information Telephone Number: 1-800-228-3877 ext.114

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENTS</u>	PERCENT	CAS NUMBER	OSHA PEL	ACGIH TLV
Filler Material				
Polyethylene Terephthalate	> 48%	4003-68-3	N/A	N/A
Wood Pulp	> 48%	9004-34-6	N/A	N/A
Polyester	< 5%	N/A	N/A	N/A
Titanium Dioxide	< 1%	13463-67-7	15mg/m ³	10mg/m ³
			(8 hour TWA)	(8 hour
TWA)				
Sleeve Material				
Cotton	55%	N/A	N/A	N/A
Polyethylene Terephthalate	45%	4003-68-3	N/A	N/A

[NOTE: exposure limits (29 CFR 1910.1200) 8 hours. TWA (ppm)]

SECTION III: HAZARDS IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

No adverse health effects are anticipated with normal use of this product.

SECTION IV: FIRST AID MEASURES

EYE CONTACT: if outer material is punctured, direct eye contact may cause minor physical or mechanical

irritation. Flush with water for 15 minutes. If irritation persists, contact physician.

SKIN CONTACT: No special procedures – if sock becomes open, wash hands with soap and water.

INHALATION: No special procedures INGESTION: No known hazards

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT: $> 400^{\circ}$ C (752° F) AUTO IGNITION: $> 300^{\circ}$ C (572° F)

FLAMMABLE LIMITS: N/A

FIRE EXTINGUISHING MEDIA: If unused: Water, Foam, CO2, Dry Chemical

If used: Refer to MSDS for absorbed liquids. Sock does not render

liquids non-flammable, neutral or less-hazardous.

SPECIAL FIRE FIGHTING PROCEDURES: None for unused socks. For used socks, refer to MSDS for absorbed

liquids. Sock does not render liquids non-flammable, neutral or less-

hazardous.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Some carbon monoxide formation is possible in oxygen lean

conditions. Refer to MSDS for absorbed liquids. Sock does not

render liquids non-flammable, neutral or less-hazardous.

SECTION VI: ACCIDENTAL RELEASE MEASURES

If material is unused: no special procedures

If used: Refer to MSDS for absorbed liquids. Sock does not render liquids non-flammable, neutral or less-

hazardous.

SECTION VII: HANDLING AND STORAGE

Store in dry area. Do not store near open flame or high heat. Socks do not render liquids non-flammable or non-hazardous. Refer to MSDS for absorbed liquids.

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION:

VENTILATION:

PROTECTIVE GLOVES:

EYE PROTECTION:

OTHER PROTECTIVE EQUIPMENT (SPECIFY):

None required

None required

None Required

SECTION IX: PHYSICAL DATA

APPEARANCE AND ODOR: Light Blue & virtually odor free

SPECIFIC GRAVITY: $0.1 \text{ to } 0.3 \text{ (H}_2\text{O} = 1)$

BOILING POINT (C): N/A

MELTING POINT (C): > 250°C (482°F)
SOLUBILITY IN WATER: Insoluable

PERCENT VOLATILE BY VOLUME: N/A EVAPORATION RATE: N/A VAPOR PRESSURE (mm Hg): N/A VAPOR DENSITY (Air = 1): N/A

SECTION X: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non-Hazardous and therefore not Regulated by DOT

SECTION XI: WASTE XI DISPOSAL METHOD

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION XII: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: April 29, 2002

REVIEWED (no changes): February 2014

PREPARED BY: SpillTech, Telephone Number: 1-800-228-3877.