



SpillTech
 5440 McGinnis Village Place
 Suite 102
 Alpharetta, GA 30005
 Phone: 1-800-228-3877
 Fax: 1-800-872-3764
 www.spilltech.com

SPILLTECH

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: HazMat Pouch or HazMat Pouch Kit
ITEM NAME: SPKHZ-5OP, OP25, OP210
CHEMICAL FAMILY: Olefin

(Because the material of the Outer Bag and the Inner Pouch do not qualify as requiring an MSDS, all specs listed below apply to the inner sorbent material only. The Outer Bag and the Inner Pouch are listed under components for clarity only.)

Company Profile:

SpillTech
 1627 O'Donoghue Street
 Mobile, AL 36615

Customer Service Telephone Number: 1-800-228-3877
Technical Information Telephone Number: 1-800-228-3877 ext. 120

SECTION II: HAZARDOUS INGREDIENTS

<u>Components</u>	<u>wt. %</u>	<u>CAS Registry #</u>
Polypropylene (Inner Filler)	85%	9003-07-0
Polyethylene (Outer Bag)	12%	9002-88 -4
Proprietary Material (Inner Pouch)	3%	Not available

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):

EXPOSURE LIMITS 8 hrs. TWA (ppm)

OSHA	PEL	ACGIH	TLV
Polypropylene	N.E.	N.E.	N.E.
Polyethylene	N.E.	N.E.	N.E.

N.E. = Not Established

SECTION III: HAZARDS IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0
FLAMMABILITY: 1
REACTIVITY: 0

*Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

SECTION IV: FIRST AID MEASURES

Eye Contact: Flush with water for 15 minutes. Consult a physician.

Ingestion: Not applicable

Inhalation: Not applicable

Skin Contact: Not applicable

SECTION V: FIRE FIGHTING MEASURES

Flash Point: Not available

Method: Not applicable

Auto Ignition Temperature: 825° F (440° C)

Flammable Limits: Not applicable

Conditions of Flammability: Not established

Explosive Properties: Not applicable

Extinguishing Media:

Unused form: Not applicable

Used form: that which is compatible to liquid(s) absorbed.

Special Fire Fighting Procedures: Wear a self-contained breathing apparatus and refer to absorbed liquid(s) MSDS(s).

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, acrolein, ketones, aldehydes and other unidentified organic compounds may be formed upon combustion.

Unusual Hazards: Refer to absorbed liquid(s) MSDS(s). SpillTech Absorbents do not render liquids nonflammable, neutral or less hazardous.

SECTION VI: ACCIDENTAL RELEASE MEASURES

No special steps to be taken if material is spilled or released.

SECTION VII: HANDLING AND STORAGE

Handling and Storage Precautions: None

Storage Temperature: Store in a cool, dry place.

Storage Pressure: Not applicable

Shelf Life: Indefinitely - as long as product is kept in a clean, dry place away from direct sunlight.

General: Refer to absorbed liquid(s) MSDS(s). SpillTech Absorbents do not render liquids nonflammable, neutral or less hazardous.

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

Engineering Controls: None required

PERSONAL PROTECTION

Eyes: Safety glasses with side shields is a good industrial practice

Respirator: Not required.

Gloves: Not normally required. However, use of cloth, canvas or leather gloves is a good industrial practice.

Other: None required.

SECTION IX: PHYSICAL DATA

Appearance: grayish in color

Physical State: Solid

Odor: No odor

Odor Threshold: Not applicable

Vapor Pressure: Not applicable

Vapor Density: Not applicable

Specific Gravity: 0.9

Solubility in Water: Insoluble

Coefficient of Water/Oil Distribution: Not available

pH: Not applicable

Boiling Point: Not applicable

Evaporation Rate: Not applicable

Melting Point: 320° F (160° C)

SECTION X: TRANSPORT INFORMATION

DOT (Department of Transportation):

Proper Shipping Name: Not regulated

Hazard Class: Not regulated

Identification Number: Not applicable

SECTION XI: WASTE DISPOSAL METHOD

Waste Disposal Method: If unused, no special precautions are necessary. Dispose of in accordance with federal, state and local regulations. In certain types of cleanup applications the nature of the material recovered will classify the resulting spent material as a hazardous component. In such instances the material should be disposed of via an approved hazardous waste disposal service and the appropriate manifesting obtained.

SECTION XII: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: December 15, 2008

REVIEWED (no changes): February 2014

PREPARED BY: SpillTech, Telephone Number: 1-800-228-3877.