

# Universal Protector® SplitRolls #GRSL150M - 15" x 150', 2 rolls/package



Tough MultiLaminate mat stands up to punishing applications.

- Abrasion-resistant outer layers of SpunBond material add durability for long life
- Low-linting gray mat is a great choice for lining tool benches, wiping down machinery or cleaning oily tools and parts
- Perfect for industrial applications in demanding environments where durability is most important
- Perforations allow you to tear rolls into different sizes based on your application
- Rolls are ideal for covering large areas

# **GRSL150M Specifications**

**Dimensions:** 15" W x 150' L

14" W x 30" L x 14" H Shipping

**Dimensions:** 

Sold as: 2 rolls per package

Color: Gray

Composition: Polypropylene

Up to 44.4 gal. per package Absorbency:

Weight: 20.4 lbs.

# per Pallet: 21

**Basis Weight:** MediumWeight

Incinerable: Yes **Ship Class:** 175

# **Metric Equivalent Specifications**

**Dimensions:** 38.1cm W x 46m L

Shipping 35.6cm W x 76.2cm L x 35.6cm H

**Dimensions:** 

Absorbency: Up to 168.1 L per package

Weight: 9.3 kg



Online: spilltech.com

Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other)

Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com

## **GRSL150M Technical Information**

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

#### **Regulations and Compliance:**

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

29 CFR 1910.22(a)(2) - Floors in your workplace should be, "maintained in a clean and, so far as possible, a dry condition."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

### **Technical Documents:**

(Available at spilltech.com)

Product Data Sheet (PDS) Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com