

## Universal Poly Blend Socks #GSO410 - 3" x 48", 10 socks/package



Universal Socks are solid performers in a variety of situations.

- Durable, universal-application, 100% poly blend-filled Socks absorb oils, coolants, solvents and water. Use them wherever you have a variety of spills and only want to stock one sock to cover everything.
- Ideal for surrounding spilled fluids or wrapping around leaky machines.
- Easy and convenient to put into place.
- Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards.
- Flexible to conform around machine bases and offer a snug fit with no seepage.
- Color-coding helps you visually identify the right sorbent for your needs. Gray signifies Universal sorbency.
- Note: These items are not compatible with sulfuric acid.

### GSO410 Specifications

<b>Dimensions:</b>	ext. dia. 3" x 48" L
<b>Shipping Dimensions:</b>	11.25" W x 22.5" L x 15.5" H
<b>Sold as:</b>	10 socks per package
<b>Color:</b>	Gray
<b>Composition:</b>	Poly Blend
<b>Recycled Content:</b>	100% Post-Industrial Recycled Poly Blend Filler
<b>Absorbency:</b>	Up to 8.33 gal. per package
<b>Absorbency per:</b>	Up to 106.6 oz. per sock
<b>Weight:</b>	10 lbs.
<b># per Pallet:</b>	35
<b>Incinerable:</b>	Yes
<b>Ship Class:</b>	175

### Metric Equivalent Specifications

<b>Dimensions:</b>	ext. dia. 7.6cm x 121.9cm L
<b>Shipping Dimensions:</b>	28.6cm W x 57.2cm L x 39.4cm H
<b>Absorbency:</b>	Up to 31.5 L per package
<b>Absorbency per:</b>	Up to 3.2 L per sock
<b>Weight:</b>	4.5 kg

## GSO410 Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



**SpillTech**

Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)