

Containment Berm #PAC1250 - 12' x 50' x 12", 1 each/package



Large-sized Berm is ideal for large-scale spill containment beneath tanker trucks, roll-off containers and more.

- One-piece design permits immediate response, compact storage and transport
- Just fold down the sidewalls and drive right in for instant containment
- · Simply clean and store after use
- Highly portable
- Features excellent rip, tear and puncture resistance for demanding applications and rough terrain
- Repairable and compatible with acids, water, oils and solvents, the Berm can be cleaned after use and stored for future use
- Note: This item is drop-shipped from vendor

PAC1250 Specifications

Dimensions: 12' W x 50' L x 12" H **Shipping** 48" W x 52" L x 20" H

Dimensions:

Sold as: 1 per package

Color: Black

Composition: Reinforced Geomembrane **Sump Capacity:** 4488 gal. per package

Weight: 232 lbs.
Incinerable: No
Ship Class: 125

Metric Equivalent Specifications

Dimensions: 3.7m W x 15m L x 30.5cm H

Shipping 121.9cm W x 132.1cm L x 50.8cm H

Dimensions:

Sump Capacity: 16987.1 L per package

Weight: 105.2 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

PAC1250 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

Technical Documents:

(Available at **spilltech.com**)
Product Data Sheet (PDS)
Chemical Compatibility (CCG)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com