

Oil-Only Spill Kit Kaddie #SPKO-KAD2 - Absorbs up to 27.7 Gallons



Be prepared for fast response with a SpillTech® Oil-Only Spill Kit!

- Roll quickly to any spill with a fully-stocked Spill Kit
- SpillTech Absorbents are easily accessible from wide doors
- Features a rear step and ergonomic handle that makes it easy to roll Kit to the spill
- Tip-back design and tough wheels allows Kit to maneuver effortlessly throughout your facility, even through doorways
- Hi-viz yellow makes Kaddie easy to see in any environment
- Packed with Oil-Only absorbents to soak up oils and oil-based liquids, but not water



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

SPKO-KAD2 Specifications

Dimensions:	23.5" W x 24" L x 38" H
Shipping	24.5" W x 23.5" L x 40" H
Dimensions:	
Sold as:	1 per package
Absorbency:	Up to 27.7 gal. per package
Weight:	59.66 lbs.
# per Pallet:	8
Incinerable:	No
Ship Class:	175
Includes:	100 - 10" x 14" White Oil-Only HeavyWeight FineFiber Pads (WPF1014H) 6 - 3" x 4' White Oil-Only Sorbent Socks (WSO430) 4 - 8" x 18" White Oil-Only Sorbent Pillows (WPIL818) 1 - 6" Glow Light Stick (A- LIGHTSTICKS) 1 - Emergency Response GuideBook (A-EGB) 5 - 18" X 30" Yellow Disposal Bags & Ties (A-DISPAG-SM) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - 3" x 5" Vinyl Spill Kit Label (A- KITLABEL) 1 - 40" x 20" x 20" Yellow Kaddie (A- KADDIE) 6 - 6" x 2" TamperProof Seals (A- SEAL) 1 - 7" Epoxy Stick (A-EPOXY)

Metric Equivalent Specifications

Dimensions:	60cm W x 61cm L x 97cm H
Shipping	62cm W x 60cm L x 102cm H
Dimensions:	
Absorbency:	Up to 104.8 L per package
Weight:	27.1 kg



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

SPKO-KAD2 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com