

## Containment Berm - L Bracket #BERM1225L - 12' x 25' x 1', 1 each/package



Provide large-scale containment that helps meet regulations with this durable, drive-in berm.

- Reinforced Coolguard® fabric resists rips, tears and punctures; highly durable for demanding applications
- Chemical-resistant berm is compatible with acids, water, oils and solvents
- Sidewalls are supported by sturdy L-shaped composite brackets
- Great for long-term containment of drums, totes, roll-offs, equipment and vehicles; also ideal for decon stations or response to tank leaks
- Reusable berm can be repaired if damaged; clean, fold and store for future deployment

### BERM1225L Specifications

<b>Dimensions:</b>	25' W x 12' L x 1' H
<b>Shipping Dimensions:</b>	40" W x 48" L x 14" H
<b>Sold as:</b>	1 per package
<b>Color:</b>	Black
<b>Composition:</b>	Coolguard® Fabric 36 mil / Composite Brackets
<b>Sump Capacity:</b>	2244 gal. per package
<b>Weight:</b>	100 lbs.
<b># per Pallet:</b>	6
<b>Incinerable:</b>	No
<b>Ship Class:</b>	125

### Metric Equivalent Specifications

<b>Dimensions:</b>	8m W x 3.7m L x 30.5cm H
<b>Shipping Dimensions:</b>	101.6cm W x 121.9cm L x 35.6cm H
<b>Sump Capacity:</b>	8493.5 L per package
<b>Weight:</b>	45.4 kg

## BERM1225L Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

### Technical Documents:

(Available at [spilltech.com](https://spilltech.com))

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



Online:  
[spilltech.com](https://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)