



**Spill**Tech

Large-scale, drive-in containment helps meet regulations without breaking your budget.

- 40-mil LLDPE construction is lightweight for easy handling, storage and transportation
- Chemical-resistant berm is compatible with acids, water, oils and solvents
- Sidewalls are supported by sturdy L-shaped composite brackets
- Great for containment of drums, totes, equipment and vehicles; also ideal for decon stations or response to tank leaks

## **BERM68E Specifications**

Dimensions:	6' W x 8' L x 1' H
Shipping	40" W x 48" L x 14" H
Dimensions:	
Sold as:	1 per package
Color:	Black
Composition:	40 mil LLDPE / Composite Brackets
Sump Capacity:	359 gal. per package
Weight:	24 lbs.
# per Pallet:	12
Incinerable:	No
Ship Class:	250

## **Metric Equivalent Specifications**

Dimensions:	182.9cm W x 2.4m L x 30.5cm H
Shipping	101.6cm W x 121.9cm L x 35.6cm H
Dimensions:	
Sump Capacity:	1358.8 L per package
Weight:	10.9 kg



Online: spilltech.com Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other)



Email: sales@spilltech.com

# **BERM68E Technical Information**

#### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

#### **Regulations and Compliance:**

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

### **Technical Documents:**

(Available at spilltech.com) Product Data Sheet (PDS) Safety Data Sheet (SDS) Chemical Compatibility (CCG)





Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com