Universal Black Duffle Spill Kit #SPKU-BLK-BG - Absorbs up to 9 Gallons



Be prepared for fast response with a SpillTech® Universal Spill Kit!

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

6455 East Johns Crossing, Suite 375 • Johns Creek GA 30097

© 2024 SpillTech Environmental Corporation. All rights reserved.

SPKU-BLK-BG Specifications

Dimensions:	11" W x 18" L x 11" H
Shipping Dimensions:	16.5" W x 25" L x 11" H
Sold as:	1 per package
Absorbency per:	Up to 9 gal.
Weight:	10.39 lbs.
# per Pallet:	35
Incinerable:	No
Ship Class:	175
Includes:	15 - 10" X 14" Gray Universal HeavyWeight FineFiber Pads (GPF1014H) 2 - 3" X 4' Gray Universal Sorbent Socks (GSO430) 2 - 18" x 18" Gray Universal Sorbent Pillows (GPIL1818) 1 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 1 - Light Stick (A-LIGHTSTICKS) 2 - 18" X 30" Yellow Disposal Bag & Tie (A-DISPBAG-SM) 1 - 18" x 11" x 11" Black Duffle Bag (A-BLACKBAG)

Metric Equivalent Specifications

Dimensions:	27.9cm W x 45.7cm L x 27.9cm H
Shipping Dimensions:	41.9cm W x 63.5cm L x 27.9cm H
Absorbency per:	Up to 34.1 L
Weight:	4.7 kg

SPKU-BLK-BG Technical Information

Warnings & Restrictions:
There are no known warnings and restrictions for this product.

Regulations and Compliance:
49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation…so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:
(Available at **spilltech.com**)
Product Data Sheet (PDS)

© 2024 SpillTech Environmental Corporation. All rights reserved.