

Drive Over Build Your Own Berm® Straight Section #DOBYOB-2S - 12' x 5.5" x 2", 1/package



Contain and control liquid in high-traffic areas.

- Customizable containment barriers pop right back to form after vehicles, pallet jacks or dollies roll over them
- Berm compresses to approximately 1/4" when driven over; constructed of 40-ounce, vinyl-coated fabric with an open-cell foam core
- 2" height accommodates low-clearance traffic
- Durable enough to withstand indoor or outdoor traffic from trucks, loaded tow motors and other heavy vehicles
- Included: 6 - 4'L x 1/8"H x 1"W Aluminum Mounting Strips & 33 - 1/4" x 1-5/8" Galvanized Steel Anchors

DOBYOB-2S Specifications

Dimensions:	5.5" W x 12' L x 2" H
Shipping Dimensions:	9" W x 48" L x 9" H
Sold as:	1 per package
Color:	Orange
Composition:	Cover - 40 oz Vinyl Coated Fabric Core - Open-Cell Polyurethane Foam Strips - Aluminum Anchors - Galvanized Steel
Weight:	11.5 lbs.
# per Pallet:	32
Incinerable:	No
Ship Class:	175

Metric Equivalent Specifications

Dimensions:	14cm W x 3.7m L x 5.1cm H
Shipping Dimensions:	23cm W x 122cm L x 23cm H
Weight:	5.2 kg

DOBYOB-2S Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Chemical Compatibility (CCG)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com