

Foam Wall Economy Containment Berm #BERM1250FE - 12' x 50' x 4", 1 each/package



Foam berms offer drive-in capability and outstanding containment capacity.

- Soft foam sidewalls allow you to roll in equipment or vehicles with minimal set up
- Capture and contain leaks, drips or spills from drums, tanks, totes, equipment or vehicles
- Use for frac tanks, vehicle washdown, refueling areas and secondary containment areas
- Low profile 4" walls compress under equipment then bounce back into shape
- Simply unfold and use; No setup needed
- · Easy cleaning and storage
- Designed for repeated use
- Made with 45mil Reinforced Polyethylene (RPE), which is lightweight and highly chemically compatible

BERM1250FE Specifications

Dimensions: 50' W x 12' L x 4" H **Shipping** 48" W x 72" L x 75" H

Dimensions:

Sold as: 1 per package

Color: Black

Composition: 45mil Reinforced Polyethylene/Built in

Foam Sidewalls

Sump Capacity: 1496 gal. per package

Weight: 200 lbs.

per Pallet: 2
Incinerable: No
Ship Class: 300

Metric Equivalent Specifications

Dimensions: 15m W x 3.7m L x 10.2cm H

Shipping 121.9cm W x 182.9cm L x 190.5cm H

Dimensions:

Sump Capacity: 5662.4 L per package

Weight: 90.7 kg



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

BERM1250FE Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

Technical Documents:

(Available at **spilltech.com**)
Product Data Sheet (PDS)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other)

Email: sales@spilltech.com