

# **Oil-Only Tote Spill Kit #SPKO-GTOTE - Absorbs up to 4.6 Gallons**



Be prepared for fast response with a high-visibility SpillTech® Oil-Only Spill Kit!

- Durable, water-resistant vinyl bag with zipper keeps contents clean and dry
- Packed with a variety of quality SpillTech® Oil-Only sorbents to handle nearly any type of small oil and other petroleum-based fluids — while repelling water
- Bright green kit stands out, even in low light conditions
- Compact design is perfect for use in trucks or other equipment
- Sturdy handles for easy carrying and hanging







Email: sales@spilltech.com

# **SPKO-GTOTE Specifications**

Dimensions:	15" W x 20" L x 4" H	Dimensions:	38cm W x 51cm L x 10cm H
Shipping	15" W x 20" L x 4" H	Shipping	38cm W x 51cm L x 10cm H
Dimensions:		Dimensions:	
Sold as:	1 per package	Absorbency:	Up to 17.4 L per package
Absorbency:	Up to 4.6 gal. per package	Weight:	2.1 kg
Weight:	4.58 lbs.		
# per Pallet:	80		
Incinerable:	No		
Ship Class:	175		
Includes:	<ul> <li>10 - 15" x 19" White Oil-Only HeavyWeight SonicBonded Pads (WPB100H)</li> <li>2 - 3" x 4' White Oil-Only Sorbent Socks (WSO430)</li> <li>2 - 18" x 30" Yellow Disposal Bag &amp; Tie (A-DISPBAG-SM)</li> <li>1 - Pair NItrile Gloves (A-GLV-NIT)</li> <li>1 - Safety Goggles (A-GOG)</li> <li>1 - 20" x 15" x 4" Green Tote Bag (A-GTOTE)</li> </ul>		

**Metric Equivalent Specifications** 

## **SPKO-GTOTE Technical Information**

## Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### **Regulations and Compliance:**

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

### **Technical Documents:**

(Available at spilltech.com)

Product Data Sheet (PDS)



Online: spilltech.com



Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com