

2 Drum Roll Top Hardcover No Drain #HARDTOP2-ND - Without Drain 1/package



Store hazardous drums safely outdoors with pumps and funnels in place!

- NOTE: The Item number for this product has recently changed from ULT9612 to HARDTOP2-ND. Please make a note of it.
- Extra headspace easily accommodates rotary drum pumps and large conical funnels
- Low-profile containment pallet positions drum tops at a safe, convenient level to pour wastes into funnels or use drum pumps
- 100% polyethylene construction will not rust or corrode
- Roll-top covers can be easily lifted from waist height to access drum tops; no need to reach near ground level
- Swing out lower doors provide full access to drums for loading and unloading
- Lockable with a standard padlock; safely lifted by forklift with drums in place
- Optional loading ramp (HTRAMP) with non-slip surface stores neatly inside when not in use — even when loaded with two 55-gallon drums
- Also available with drain plug (HARDTOP2-WD) to let you empty sump without relocating stored containers



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com

HARDTOP2-ND Specifications

Dimensions:	41.25" W x 67.25" L x 74" H
Shipping	48" W x 72" L x 81" H
Dimensions:	
Sold as:	1 per package
Color:	Yellow
Composition:	100% Polyethylene
Load Capacity UDL:	4500 lbs. per package
Sump Capacity:	66 gal. per package
Weight:	355 lbs.
# per Pallet:	1
Incinerable:	No
Ship Class:	250

Metric Equivalent Specifications

Dimensions:	105cm W x 171cm L x 188cm H
Shipping	122cm W x 183cm L x 206cm H
Dimensions:	
Load Capacity UDL:	2041.2 kg per package
Sump Capacity:	249.8 L per package
Weight:	161 kg

HARDTOP2-ND Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

40 CFR 264.175 - Hazardous waste containment systems must be free of structural cracks or gaps; designed to keep spilled liquids from remaining in contact with the container; prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers or the volume of the largest container, whichever is greater." For example, four 55-gallon drums require secondary containment of 55 gallons.

40 CFR 122.26 - Facilities must have a detailed plan in place to prevent illegal discharge of pollutants into waterways.

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
sales@spilltech.com