

# HazMat Foil Bag Spill Kit #SPKHZ-FOILB - Absorbs up to 4.8 Gallons



Be prepared for fast response with a SpillTech® HazMat Spill Kit!

- Packed with quality SpillTech® products to help you clean up fast and comply with regulations
- Includes a variety of sorbents to handle nearly any type of smaller caustic, hazardous or unknown spill — including acids, bases, solvents and chemicals — that truckers encounter on a regular basis
- Self-contained, compact Kit provides easy access when quick response is necessary
- Heat-sealed bag allows you to determine if the kit has been used or not
- Bag is puncture-proof, water- and UV-resistant

## **SPKHZ-FOILB Specifications**

**Dimensions:** 21" W x 7.5" D x 20" L **Shipping** 19" W x 19" L x 7" H

**Dimensions:** 

Sold as: 1 per package

**Absorbency:** Up to 4 gal. per package

Weight: 5.21 lbs.
# per Pallet: 100
Incinerable: No
Ship Class: 175

Includes: 15 - 15" X 19" Yellow HazMat

Sorbent Pads (YPB200S)

3 - 3" X 4' Yellow HazMat Sorbent

Socks (YSO430)

2 - 18" X 30" Yellow Disposal Bag &

Tie (A-DISPBAG-SM)

Pair Nitrile Gloves (A-GLV-NIT)
 Safety Goggles (A-GOG)
 20" X 21" X 7.5" Foil Bag (A-

FOILB)

## **Metric Equivalent Specifications**

Dimensions: 53cm W x 19cm D x 51cm L Shipping 48cm W x 48cm L x 18cm H

**Dimensions:** 

**Absorbency:** Up to 15.1 L per package

Weight: 2.4 kg

### **SPKHZ-FOILB Technical Information**

#### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### **Regulations and Compliance:**

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

#### **Technical Documents:**

(Available at spilltech.com)

Product Data Sheet (PDS)

