

## DrainCover #ADC12-CIR - 12" Round 1 each/package



Seal unwanted liquids out of your drain by covering it with a flexible DrainCover.

- Solid polyurethane covers are tacky on both sides so either can form a tight seal to block contaminants
- More chemical resistant than rubbers or plastics, DrainCover stands up to a wide range of chemicals, solvents and oils
- Reusable; can be washed then stored in the handy, portable box
- Note: Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Customer Service at 800.228.3877 or use our live chat feature. These products are for temporary use only. Pick up after each use, clean, then store properly. Do not leave down for extended periods of time or drive over with vehicles.

### ADC12-CIR Specifications

<b>Dimensions:</b>	ext. dia. 12" x 0.5" D
<b>Shipping Dimensions:</b>	12.5" W x 12.5" L x 1.5" H
<b>Sold as:</b>	1 per package
<b>Color:</b>	Red
<b>Composition:</b>	Polyurethane
<b>Weight:</b>	2 lbs.
<b># per Pallet:</b>	40
<b>Incinerable:</b>	No
<b>Ship Class:</b>	70

### Metric Equivalent Specifications

<b>Dimensions:</b>	ext. dia. 30.5cm x 12.7mm D
<b>Shipping Dimensions:</b>	31.8cm W x 31.8cm L x 3.8cm H
<b>Weight:</b>	.9 kg

## ADC12-CIR Technical Information

### Warnings & Restrictions:

#### Urethane Notice

Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity, and UV radiation. Typical life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. For more details and for chemical compatibility, please call Customer Service at 800.228.3877 or use our live chat feature. These products are for temporary use only. Pick up after each use, clean, then store properly. Do not leave down for extended periods of time or drive over with vehicles.

### Regulations and Compliance:

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

### Technical Documents:

(Available at [spilltech.com](https://spilltech.com))

Product Data Sheet (PDS)

Safety Data Sheet (SDS)

Chemical Compatibility (CCG)



Online:  
[spilltech.com](https://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[sales@spilltech.com](mailto:sales@spilltech.com)